

# OPEN POCKET SOFT MOUNT

## HIGH SPEED WASHER-EXTRACTOR

Equipped with the revolutionary  
DynOzone - DynaWash® Ozone System.

**DynOzone**

# CSL60



### INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model	CSL60
Capacity	60 lb.
Cylinder Size	32" x 20"
Cubic Content	9.3 cu. ft.
Door Opening	25"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	4" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 810 RPM
G-Force at High Extract	up to 297 G
Extract Motor	3 kW
Circuit Breaker	30 Amp
Control	HMi Touch Screen
Programs	50
Features	Productivity Reporting
<b>Dimensions</b> (overall)	
Width	46"
Depth	51"
Height	61"
Net Weight	3,300 lb.
Shipping Weight	3,410 lb.



Model shown with optional forward tilting and autoswing door.  
Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

[www.edrodynawash.com](http://www.edrodynawash.com)

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements