

# THREE POCKET RIGID MOUNT WASHER-EXTRACTORS

Equipped with the revolutionary  
DynOzone - DynaWash® Ozone System.



**DynOzone**

## INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model Number	DW100	DW150	DW200	DW300	DW400
<b>Dry Weight Capacity:</b> Pounds	100	150	200	300	400
<b>Cylinder Volume:</b> Cubic Feet	20.05	27.21	34.54	51.59	68.69
Diameter x Depth	42" x 25"	48" x 26"	48" x 33"	54" x 42"	60" x 42"
Water Inlets (H&C)	1-1/4" NPT	2" NPT	2" NPT	2" NPT	2" NPT
Drain	4" N.O.	6" N.O.	6" N.O.	8" N.O.	8" N.O.
Direct Steam Inlet	1"	1"	1"	1"	1"
Inverter Motor HP	10 HP	15 HP	20 HP	30 HP	40 HP
G-Force at Hi Extract	232 G	237 G	288 G	299 G	306 G
Circuit Breaker (220/3/60)	30 AMP	30 AMP	50 AMP	80 AMP	100 AMP
<b>Overall Dimensions*</b> RIGID MOUNT (DW)	<b>DW100</b>	<b>DW150</b>	<b>DW200</b>	<b>DW300</b>	<b>DW400</b>
Width	62"	76"	68"	80"	85"
Depth	45"	48"	57"	68"	71"
Height	74"	74"	76"	84"	92"
Net Weight	2,600-pounds	3,000-pounds	3,200-pounds	4,500-pounds	6,300-pounds

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Overall dimensions are space dimensions required to place and operate machine.  
Consult factory for installation drawings for specific models.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

[www.edrodynawash.com](http://www.edrodynawash.com)

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

AHDWPDF:0309