

PASSTHRU RIGID MOUNT

WASHER-EXTRACTORS

Equipped with the revolutionary
DynOzone - DynaWash® Ozone System.

DynOzone



INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model Number	DW100PT	DW150PT	DW200PT	DW300PT	DW400PT
Dry Weight Capacity: Pounds	100	150	200	300	400
Cylinder Volume: Cubic Feet	20.05	27.21	34.54	51.59	68.69
Diameter x Depth	26" x 18"	32" x 20"	39" x 26"	45" x 32"	45" x 32"
Water Inlets (H&C) Drain	1-1/4" NPT 4" O.D.	2" NPT 6" O.D.	2" NPT 6" O.D.	2" NPT 8" O.D.	2" NPT 8" O.D.
Direct Steam Inlet	1"	1"	1"	1"	1"
Inverter Motor HP	5.5 HP	7.5 HP	7.5 HP	15 HP	15 HP
G-Force at Hi Extract	232 G	229 G	229 G	232 G	248 G
Circuit Breaker (220/3/60)	30 AMP	50 AMP	50 AMP	100 AMP	100 AMP
Overall Dimensions* RIGID MOUNT (DW_PT)	<i>DW100PT</i>	<i>DW150PT</i>	<i>DW200PT</i>	<i>Not Available</i>	<i>Not Available</i>
Width	72"	82"	89"		
Depth	48"	48"	57"		
Height	69"	71"	71"		
Net Weight	3,100-pounds	3,600-pounds	3,800-pounds		

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Overall dimensions are space dimensions required to place and operate machine.
Consult factory for installation drawings for specific models.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN



www.edrodynawash.com

EDRO
DYNAWASH

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.
Manufactured in accordance with Canadian Standards Association general requirements

AHDWPTPDF:0309