

# PASSTHRU SOFT MOUNT WASHER-EXTRACTORS

Equipped with the revolutionary  
DynOzone - DynaWash® Ozone System.



**DynOzone**

## INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model Number	DW100PTSM	DW150PTSM	DW200PTSM	DW300PTSM	DW400PTSM
<b>Dry Weight Capacity:</b>					
Pounds	100	150	200	300	400
<b>Cylinder Volume:</b>					
Cubic Feet	20.05	27.21	34.54	51.59	68.69
Diameter x Depth	26" x 18"	32" x 20"	39" x 26"	45" x 32"	45" x 32"
Water Inlets (H&C)	1-1/4" NPT	2" NPT	2" NPT	2" NPT	2" NPT
Drain	4" N.O.	6" N.O.	6" N.O.	8" N.O.	8" N.O.
Direct Steam Inlet	1"	1"	1"	1"	1"
Inverter Motor HP	5.5 HP	7.5 HP	7.5 HP	15 HP	15 HP
G-Force at Hi Extract	232 G	229 G	229 G	232 G	248 G
Circuit Breaker (220/3/60)	30 AMP	50 AMP	50 AMP	100 AMP	100 AMP
<b>Overall Dimensions*</b>					
SOFT MOUNT (DW_PTSM)	<i>DW100PTSM</i>	<i>DW150PTSM</i>	<i>DW200PTSM</i>	<i>DW300PTSM</i>	<i>DW400PTSM</i>
Width	96"	82"	89"	109"	114"
Depth	48"	48"	57"	70"	71"
Height	70"	71"	71"	81"	89"
Net Weight	5,200-pounds	7,000-pounds	7,380-pounds	9,375-pounds	12,200-pounds

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Overall dimensions are space dimensions required to place and operate machine.  
Consult factory for installation drawings for specific models.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

[www.edrodynawash.com](http://www.edrodynawash.com)

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

AHDWPTSMDF:0309