

# OPEN POCKET RIGID MOUNT

## HIGH SPEED WASHER-EXTRACTOR

Equipped with the revolutionary  
DynOzone - DynaWash® Ozone System.

**DynOzone**

# NX100



### INDUSTRIAL STRENGTH WASHER-EXTRACTOR

## SPECIFICATIONS

Model	NX100-TV
Capacity	100 lb.
Cylinder Size	36" x 27"
Cubic Content	15.7 cu. ft.
Door Opening	17"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 625 RPM
G-Force at High Extract	up to 200 G
Extract Motor	7.5 h.p.
Circuit Breaker	30 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
<b>Dimensions</b> (overall)	
Width	38"
Depth	48"
Height	69"
Net Weight	1,500 lb.
Shipping Weight	1,500 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

[www.edrodynawash.com](http://www.edrodynawash.com)

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements