

OPEN POCKET RIGID MOUNT

HIGH SPEED WASHER-EXTRACTOR

Equipped with the revolutionary
DynOzone - DynaWash® Ozone System.

DynOzone

NX140



INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model	NX140-TV
Capacity	140 lb.
Cylinder Size	42" x 27"
Cubic Content	21.6 cu. ft.
Door Opening	25"
Water Inlets (Hot & Cold)	1-1/4" NPT
Drain	2 @ 3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 575 RPM
G-Force at High Extract	up to 197 G
Extract Motor	10 h.p.
Circuit Breaker	30 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
Dimensions (overall)	
Width	46"
Depth	54"
Height	70"
Net Weight	2,300 lb.
Shipping Weight	2,400 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

www.edrodynawash.com

EDRO
DYNAWASH

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.
Manufactured in accordance with Canadian Standards Association general requirements