

# OPEN POCKET RIGID MOUNT

## HIGH SPEED WASHER-EXTRACTOR

Equipped with the revolutionary  
DynOzone - DynaWash® Ozone System.

**DynOzone**

# NX40



### INDUSTRIAL STRENGTH WASHER-EXTRACTOR

## SPECIFICATIONS



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

Model	NX40-TV
Capacity	40 lb.
Cylinder Size	30" x 16"
Cubic Content	6.5 cu. ft.
Door Opening	15"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 700 RPM
G-Force at High Extract	up to 209 G
Extract Motor	3 h.p.
Circuit Breaker	15 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
<b>Dimensions</b> (overall)	
Width	34"
Depth	33-3/4"
Height	57"
Net Weight	850 lb.
Shipping Weight	890 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Field programmable speeds.

[www.edrodynawash.com](http://www.edrodynawash.com)

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements