

OPEN POCKET RIGID MOUNT

HIGH SPEED WASHER-EXTRACTOR

Equipped with the revolutionary
DynOzone - DynaWash® Ozone System.

DynOzone

NX60



INDUSTRIAL STRENGTH WASHER-EXTRACTOR

SPECIFICATIONS

Model	NX60-TV
Capacity	60 lb.
Cylinder Size	32" x 20"
Cubic Content	9.3 cu. ft.
Door Opening	17"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 700 RPM
G-Force at High Extract	up to 222 G
Extract Motor	5 h.p.
Circuit Breaker	20 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
Dimensions (overall)	
Width	35-1/2"
Depth	44"
Height	63"
Net Weight	1,250 lb.
Shipping Weight	1,250 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

www.edrodynawash.com

EDRO
DYNAWASH

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.
Manufactured in accordance with Canadian Standards Association general requirements