

U.S. Navy Shipboard Washer-Extractor DX25N

Manufactured I/AW CID A-A-59365



INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Specifications	
Capacity	20-pound, open pocket
Cylinder Size	21" x 12-1/2"
Cubic Content	2.5 cu.ft.
Potable Water Inlets	3/4" NH, Hot & Cold
Supply Inlet	3/4" NH
Sewer Drain	2" PVC pipe
Electrical Service	440/3/60, maximum demand AMPS/10 SEC: 1.6
Wash/ Extract Motor	.17/1.0 h.p., 360/3,400 rpm, 1.0/.8 FLA
High Extract	387 RPM / 42 G
APL	910800014L
NSN	3510-01-267-1859
Dimensions (overall)	
Width	26"
Depth	24-1/2"
Height	41"
Net Weight	310-pounds

Equipped with 1 motor, 2 speed drive with single speed extract.
Class 3 Microprocessor Control.
Consult factory for Installation Data Drawing with exact foundation and
installation requirements.



DX25N



New
Microprocessor
Control

The EDRO Corporation
37 Commerce Street - P. O. Box 308
East Berlin, CT 06023-0308 USA
Fax (860) 828-5984 Phone (860) 828-0311