

# Open Pocket Rigid Mount

## High Speed Washer-Extractor

Available with revolutionary  
DynOzone - DynaWash® Ozone System.



# NX100



## INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS



<i>Model</i>	<i>NX100-P6</i>
Capacity	100 lb. (45 kg)
Cylinder Size	36" x 27" (91 cm x 68 cm)
Cubic Content	15.7 cu. ft. (445 liters)
Door Opening	17" (43 cm)
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
<b><i>Drive System</i></b>	variable speed drive
Number of Speeds	6
Wash Speed	45 RPM
High Extract	up to 625 RPM
G-Force at High Extract	up to 200 G
Extract Motor	7.5 h.p.
Circuit Breaker	50 Amp
<b><i>Control</i></b>	programmable computer
Programs	51
Operating Modes	2 <i>plus</i> manual overrides
Manual Operation	Security Key Lock
<b><i>Dimensions</i></b> (overall)	
Width	38" (96 cm)
Depth	48" (122 cm)
Height	69" (175 cm)
Net Weight	1,500 lb. (681 kg)
Shipping Weight	1,550 lb. (705 kg)

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Six speed model has four programmable extract speeds (low, medium low, medium high and high extract).

[www.edrodywash.com](http://www.edrodywash.com)

**EDRO**  
**DYNAWASH**

The EDRO Corporation

37 Commerce Street - P. O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828-5984 Phone (860) 828-0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.  
Manufactured in accordance with Canadian Standards Association general requirements



E3NX100PDF: 0605