

Open Pocket Rigid Mount

High Speed Washer-Extractor

Available with revolutionary
DynOzone - DynaWash® Ozone System.



NX140



INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS



<i>Model</i>	<i>NX140-P6</i>
Capacity	140 lb. (64 kg)
Cylinder Size	42" x 27" (107 cm x 68 cm)
Cubic Content	21.6 cu. ft. (613 liters)
Door Opening	25" (64 cm)
Water Inlets (Hot & Cold)	1-1/4" NPT
Drain	2 @ 3-1/8" O.D.
<i>Drive System</i>	variable speed drive
Number of Speeds	6
Wash Speed	40 RPM
High Extract	up to 575 RPM
G-Force at High Extract	up to 197 G
Extract Motor	10 h.p.
Circuit Breaker	60 Amp
<i>Control</i>	programmable computer
Programs	51
Operating Modes	2 <i>plus</i> manual overrides
Manual Operation	Security Key Lock
<i>Dimensions</i> (overall)	
Width	46" (117 cm)
Depth	54" (137 cm)
Height	70" (178 cm)
Net Weight	2,300 lb. (1,045 kg)
Shipping Weight	2,400 lb. (1,091 kg)

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Six speed model has four programmable extract speeds (low, medium low, medium high and high extract).

www.edrodywash.com

EDRO
DYNAWASH

The EDRO Corporation

37 Commerce Street - P. O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828-5984 Phone (860) 828-0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.
Manufactured in accordance with Canadian Standards Association general requirements



E3NX140PDF: 0605