



M-SERIES TUMBLER DRYERS

FOR U.S. NAVY SURFACE SHIPS



M80

MILITARY TUMBLER DRYER **SPECIFICATIONS**

<i>Global Specs</i>	<i>M80</i>
Capacity	80 lbs dryweight
Electrical	440/60/3
Basket Motor	1 HP
Fan Motor	1 HP
Exhaust Duct	10" DIA
Rated Air Displacement	1800-2000 CFM at 0.3" Water Static
<i>M80TDE</i>	<i>Electric Heated Modular</i>
Heat Capacity	48 kW
Total Current	67 AMPS
<i>M80TDS</i>	<i>Steam Heated Modular</i>
Steam Supply Connection	3/4"
Steam Return Connection	1"
Operating Steam Pressure	7-15 PSIG Low Pressure 125 PSIG Max High Pressure
Steam Consumption	2.7 BHP-90 lbs/Hr at Low Pressure 3.4 BPH-117.3 lbs/Hr at High Pressure
<i>Dimensions</i> (overall)	
Width	39.25"
Depth	56.5"
Height	75"
Net Weight	850 lb.
Shipping Weight	1110 lb.



www.edrodynawash.com



The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.

AHM80PDF:0810