

U.S. NAVY SUBMARINE

WASHER-EXTRACTOR



DS16-SUB

MILITARY SPEC WASHER-EXTRACTOR

SPECIFICATIONS

Specifications	
Capacity	16 lb., open pocket
Cylinder Size	21" x 12-1/2"
Cubic Content	2.5 cu. ft.
Water Inlets (Hot & Cold)	3/4" NH
Sewer Drain	2" PVC pipe
Power Supply	440/3/60
Wash / Extract Motor	0.75/0.13 kW / FLA 1.9
Extract Speed	400 RPM
NSN 3510-01-562-8394	
<i>Dimensions (machine)</i>	
Width	24-1/2"
Depth	25-1/2"
Height	33-1/2"
Net Weight (Machine)	320 lbs.
Net Weight (Control Box)	52 lbs.
Control HMi Touch Screen	
Programs	50
Features	Productivity Reporting
<i>Remote Control Box</i>	
Width	23-7/8"
Depth	9"
Height	8-1/2"
Net Weight	20 lbs.



Remote Control Box

Manufactured in accordance with MIL-DTL-23554E(SH)
 Equipped with 1 motor, 2 speed drive with single speed extract.
 Remote Control Box equipped with 20' dual cable pin connectors.
 Consult factory for installation Data Drawing with exact foundation and installation requirements.



The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

www.edrodynawash.com