

U.S. NAVY SHIPBOARD

WASHER-EXTRACTOR



DW1000CNSWE

MILITARY SPEC WASHER-EXTRACTOR

SPECIFICATIONS

Specifications

Capacity	100 lb., three pocket
Cylinder Size	42" x 24"
Cubic Content	19.24 cu. ft.
Potable Water Inlets	1-1/4" NPT, up to 150 PSI, Hot & Cold
Sewer Drain	4" NPT N.O.
Low Air Pressure	1/4" NPT @ 80-100 PSI, 3.5 cu.ft./hr.
Electrical Service	440/3/60, maximum demand AMPS/10 SEC: 34
Wash Motor	3/4 h.p., 1750 rpm, 1.4 FLA
Extract Motor	5.5/2.75 h.p., 1675/825, 8.5/7 FLA
Low Extract	300 RPM / 53 G
High Extract	600 RPM / 214 G

Model	-14A	-14B	-24A	-24B
Type	Steam	Electric	Electric	Electric
Class 4	Touch Screen	Touch Screen	Touch Screen	Touch Screen
Style	Non-Modular	Modular	Non-Modular	Modular
Heating Requirements (Steam / Electric)	3/4" NPT Supply & Return up to 125 PSI	3/4" NPT Supply & Return up to 125 PSI	36 kW	36 kW
<i>Dimensions (overall)</i>				
Width	58"	62"	58"	62"
Depth	47"	47"	47"	47"
Height	66"	69"	66"	69"
Net Weight	2,700 lbs.	2,900 lbs.	2,700 lbs.	2,900 lbs.



DW1000CNSWE-24B

Manufactured in accordance with CID A-A-59469.

Type I = Steam Heating; Type II = Electric Booster Heating

Class 4 = Touch Screen Control

Style A = non-Modular; Style B = Modular (Hatchable)

All models equipped with 2 motor, 3 speed drive with 2-speed extract.

*Dimensions rounded to nearest inch. Consult factory for Installation Data Drawing with exact foundation and installation requirements.

Consult Factory for "ER" option for installations with bulkhead or access restrictions.

Modular models breakdown to fit through a 26" x 66" ship's hatch.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN



The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

www.edrodynawash.com