

# U.S. NAVY SHIPBOARD

## WASHER-EXTRACTOR



# DW600PNSWE

MILITARY SPEC WASHER-EXTRACTOR

## SPECIFICATIONS

DW600PNSWE-24AER



DW600PNSWE-24A



Specifications				
Capacity	60 lb., three pocket			
Cylinder Size	42" x 18"			
Cubic Content	14.4 cu. ft.			
Potable Water Inlets	1 1/4" NPT, up to 150 PSI, Hot & Cold			
Sewer Drain	4" NPT N.O.			
Low Air Pressure	1/4" NPT @ 80-100 PSI, 3.5 cu.ft./hr.			
Electrical Service	440/3/60, maximum demand AMPS/10 SEC: 50			
Wash Motor	3/4 h.p., 1750 rpm, 1.4 FLA			
Extract Motor	1.5/1.5 h.p., 1725/850, 3.0/4.6 FLA			
Low Extract	300 RPM / 53 G			
High Extract	600 RPM / 214 G			
Model	-14A	-14B	-24A	-24B
Type	Steam	Electric	Electric	Electric
Class 4	Touch Screen	Touch Screen	Touch Screen	Touch Screen
Style	Non-Modular	Modular	Non-Modular	Modular
Heating Requirements (Steam / Electric)	3/4" NPT Supply & Return up to 125 PSI	3/4" NPT Supply & Return up to 125 PSI	36 kW	36 kW
<i>Dimensions (overall)</i>				
Width	58"	61"	58"	68"
Depth	42"	42"	42"	42"
Height	66"	69"	66"	69"
Net Weight	2,150 lbs.	2,350 lbs.	2,150 lbs.	2,350 lbs.

Manufactured in accordance with CID A-A-59469

Type I = Steam Heating; Type II = Electric Booster Heating

Class 4 = Touch Screen Control

Style A = non-Modular; Style B = Modular (Hatchable)

All models equipped with 2 motor, 3 speed drive with 2-speed extract.

\*Dimensions rounded to nearest inch. Consult factory for Installation Data Drawing with exact foundation and installation requirements.

Consult Factory for "ER" option for installations with bulkhead or access restrictions.

Modular models breakdown to fit through a 26" x 66" ship's hatch.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

[www.edrodynawash.com](http://www.edrodynawash.com)



The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311