

U.S. NAVY SHIPBOARD

WASHER-EXTRACTOR



NX60NSWE

MILITARY SPEC WASHER-EXTRACTOR

SPECIFICATIONS



Specifications

Capacity	60 lb., open pocket
Cylinder Size	32" x 20"
Cubic Content	9.31 cu. ft.
Potable Water Inlets	3/4" NH, Hot & Cold
Sewer Drain	3" PVC pipe
Overflow	1-1/4" internally plumbed
Electrical Service	440/3/60, maximum demand AMPS/10 SEC: 20
Extract Motor	5 h.p., 1735 rpm, 6.2 FLA
High Extract	430 RPM / 84 G

Model	-22A	-22B
Type	Electric	Electric
Class	Touch Screen	Touch Screen
Style	Non-Modular	Modular
Heating Requirements	18kW	18kW
<i>Dimensions (overall)</i>		
Width	35"	35"
Depth	48"	48"
Height	64"	64"
Net Weight	1,150 lbs.	1,150 lbs.

Manufactured in accordance with CID A-A-59365

Equipped with inverter with single motor drive.

Type II E.B.H.

Style A & B Modular Note 26" x 66"

Class 4 = Touch Screen Control

Consult factory for Installation Data Drawing with exact foundation and installation requirements.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

www.edrodynawash.com



The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311

AHNX60NSWEPDF:0409